

PURE ASPHALT CO SAFETY DATA SHEET (SDS)

SECTION 1: IDENTIFICATION

Product Name #44 Sewer Joint Compound (All Seasonal Grades)
Other Names Mastic
Use Sealing Precast Concrete Structures
Company Pure Asphalt Co.
3455 W. 31st Place
Chicago, IL 60623
Tel: (773) 247-7030
Fax: (773) 247-7066
Emergency Tel. ChemTrec 800-262-8200

SECTION 2: HAZARD(S) IDENTIFICATION

GHS HAZARD CLASSIFICATION:

Physical Hazards	Flammable Liquid	Category 3
Health Hazards	Acute Toxicity-Oral	Category 5
	Acute Toxicity-Inhalation	Category 5
	Skin Corrosion/Irritation	Category 2
	Eye Corrosion/Irritation	Category 2
	Target organ toxicity, repeat exposure	Category 2

LABEL ELEMENTS:



Signal Word

Warning

Hazard Statements

H226: Flammable liquid and vapour
H315: Causes skin irritation
H320: Causes eye irritation
H373: May cause damage to organs through prolonged or repeated exposure

Precautionary statements
Prevention

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical and lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P280: Wear protective gloves, protective clothing, eye protection, and face protection.
P260: Do not breathe mist or spray.

P270: Do not eat, drink or smoke when using this product.

P264: Wash exposed areas thoroughly after handling.

Response

P370+378: IN CASE OF FIRE: Use carbon dioxide (CO2), alcohol foam, water fog or dry chemical to extinguish. DO NOT use stream/jet of water as this will spread fire.
P303+361+ IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with 353: water or shower.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P321: Specific treatment: Apply hand or body lotion to reduce irritation.
P332+313: If skin irritation occurs: Get medical advice or attention.
P362+364: Take off contaminated clothing and wash it before reuse.
P305+351+ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if 338: present and easy to do – continue rinsing.
P337+313: If eye irritation persists get medical advice and/or attention.
P314: Get Medical advice/attention if you feel unwell.
P331: Do NOT induce vomiting.

Storage

P403+235: Store in a well ventilated place. Keep cool.

Disposal

P501: Dispose of contents and container in accordance with local, regional, national, and international regulation.

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Mixture

Chemical Name	Common Name	CAS number	Percent by weight
Petroleum Distillates	Stoddard Solvent	8052-41-3	5-25%
Petroleum Hydrocarbon	Asphalt	8052-42-4	30-60%

SECTION 4: FIRST-AID MEASURES

General Advice

Take off immediately all contaminated clothing. Get Medical advice/attention if you feel unwell. Wash contaminated clothing before reuse.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get Medical attention if you feel unwell.

Skin

Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation or a rash occurs: Get medical advice/attention.

Eye

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical attention.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get Medical advice and/or attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.
Skin irritation: May cause redness, itching and/or pain.
Inhalation of mist/vapors: Prolonged or repeated exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguisher type(s) Use carbon dioxide (CO₂), alcohol foam, water fog or dry chemical to extinguish.

Unsuitable Extinguisher type Do not use stream or jet of water as this will spread fire.

Specific hazardous arising from fire. Vaporized material may form explosive mixture with air. Thermal decomposition (burning) will produce oxides of carbon including carbon monoxide and may also produce irritating, corrosive and/or toxic gases, vapors and fumes.

Special protective equipment for fire fighting. Self-contained breathing apparatus and full protective gear must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Leak or spill procedures Remove all sources of ignition. Provide adequate ventilation.

Containment Contain and absorb with inert material. (e.g. oil dry, sand)

Cleanup Dispose in accordance with all local, state and federal regulations.

Precautions In the event of a large spill, contain material and recover for use if possible. Avoid discharge into drains, water courses and the ground.

SECTION 7: HANDLING AND STORAGE

Storage Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry and well ventilated area.

Handling Avoid prolonged or repeated skin contact and avoid breathing vapors.

Incompatible Contaminants Avoid exposure to oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	OSHA PEL	ACGIH TLV-TWA
Petroleum Distillate	500 ppm	100 ppm

Engineering Controls Use with adequate ventilation.

PPE Eye/Face: Face shield, goggles
Skin: Chemical protective gloves.
Respiratory: Level of exposure needs to be determined. If required, use a particulate filter, a NIOSH-approved air purifying respirator with organic vapor cartridge or a supplied air respirator.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Form	Paste
Color	Black
Flammability Limits	
Upper	~6%
Lower	~0.8%
Odor	Mild Petroleum Odor
Odor Threshold	Not Determined
Vapor Pressure at 20°C	<3 mm Hg, based on solvent
pH	Not applicable
Vapor Density (air=1)	>1
Evaporation Rate	Not Determined
Specific Gravity, 16°C	>1.0
Melting Point/Range	Not Determined
Boiling Point/Range	>350°F (>177°C)
Solubility	Very slight
Partition Coefficient	Not Determined
Flash Point	>105°F (>40°C) component with lowest PMCC flash point
Flammability	Class 3
Auto ignition Temperature	> 410°F (>210°C)
Decomposition Temperature	Not Determined
Viscosity	Time, temperature and shear dependent

SECTION 10: STABILITY AND REACTIVITY

Reactivity	
Chemical Stability	Stable
Other	
Hazardous Reactions	Combustion
Polymerization	Will not occur.
Conditions to Avoid	Strong oxidizing agents: sources of ignition.
Incompatible Materials	Strong oxidizing agents
Decomposition Hazards	Combustion products: Oxides of carbon, nitrogen, and sulfur and potentially irritating and/or toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Ingredient	LD50	LC50
Petroleum Distillates	Oral-Rat, > 5gm/Kg	4 Hr.-Rat, > 5500 mg/M ³
Routes of Exposure		
Inhalation	May cause damage to organs through prolonged or repeated exposure	
Ingestion	Expect low ingestion hazard. Do NOT induce vomiting. AVOID ASPIRATION.	
Skin Contact	Causes skin irritation	
Eye Contact	Causes eye irritation	

**Delayed, Immediate, and Long
Term Exposure**

Prolonged or repeated inhalation of petroleum distillates may cause damage to organs.

Carcinogenicity

None of the components of this mixture are considered to be a carcinogen by IARC, ACGIH, NTP, OR OSHA.
Bitumen fumes generated at paving temperatures in excess of 250°F (120°C) are classified by IARC as "possibly carcinogenic to humans" (Group 2B) but this product is used at ambient temperatures and does not generate fumes.

SECTION 12: ECOLOGICAL INFORMATION

Eco toxicity

This mixture contains components that are potentially toxic to freshwater and saltwater ecosystems.

Environmental Fate

This material may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper handling and disposition for disposal according to local, state, federal and international regulations.

SECTION 14: TRANSPORT INFORMATION

For Industrial/Professional Use Only-Keep out of reach of Children

Domestic (US and US to Canada)

Proper shipping name: Combustible liquid, n.o.s. (contains Mineral Spirits)

Identification Numbers: NA1993

Class or Division: Comb liq

Packing Group: III

Label Codes: None

Special Provisions: IB3, T1, T4, TP1

Packaging

Exceptions: 173.150

Non-Bulk: 173.203

Bulk: 173.241

Quantity Limitations

Passenger Aircraft/Rail: 60 L

Cargo Aircraft Only: 220L

Vessel Stowage

Location: A

Other:

International (including within Canada)

Proper shipping name: Petroleum products, n.o.s.

Identification Numbers: UN1268

Class or Division: 3
Packing Group: III
Label Codes: 3
Special Provisions: 144, B1, IB3, T4, TP1, TP29

Packaging

Exceptions: 173.150
Non-Bulk: 173.203
Bulk: 173.242

Quantity Limitations

Passenger Aircraft/Rail: 60 L
Cargo Aircraft Only: 220L

Vessel Stowage

Location: A
Other:

Transport in Bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

TSCA	All components are on the TSCA inventory.
Sara Title III, Section 313	No, None
Sara Title III, Section 311, 312	Fire Hazard

SECTION 16: OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.