### SAFETY DATA SHEET

Revision Date 24-Apr-2015

Version 1

### SECTION OF THE PROPERTY OF THE

Product identifier

**Product Name** 

765-1188 NAPA THREAD SEALANT W/PTFE (PTX80632) 4 FL.OZ

Other means of identification

**Product Code** 

21127

Synonyms

None

Recommended use of the chemical and restrictions on use

Recommended Use

Sealant

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Hartford, CT 06106 USA

**Distributor** 

**ITW Permatex** 

ITW Permatex Canada

10 Columbus Blvd.

35 Brownridge Road, Unit 1 Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

**Company Phone Number** 

1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency:

00+1+813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

### 2. HAZARDS IDENTIFICATION

### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral Category 4 Carcinogenicity Category 2	
Cardinogenioty	
Specific target organ toxicity (single exposure)  Category 1	
Flammable liquids Category 3	

#### Label elements

**Emergency Overview** 

### Danger

Harmful if swallowed May cause cancer Causes damage to organs Flammable Liquid



Appearance White

Physical state Paste

Odor Alcoholic

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Take precautionary measures against static discharge

### **Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use Water spray, fog or regular foam for extinction

### **Precautionary Statements - Storage**

Store locked up

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

Harmful to aquatic life with long lasting effects.

Unknown acute toxicity

65.99515% of the mixture consists of ingredient(s) of unknown toxicity

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
TALC	14807-96-6	15 - 40	. *
ETHANOL	64-17-5	10 - 30	*
CASTOR OIL	8001-79-4	10 - 30	*
POLYVINYL RESIN	63148-65-2	· 5 - 10	*
2-PROPANOL	67-63-0	1-5	*
TITANIUM DIOXIDE	13463-67-7	1-5	*
METHANOL	67-56-1	1 - 5	*
POLYTETRAFLUOROETHYLENE	9002-84-0	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### HERE ELECTION OF THE PARTY OF T

### Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with soap and water. If symptoms persist, call a physician.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

### Most important symptoms and effects, both acute and delayed

**Symptoms** 

See section 2 for more information.

### Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

### FINE FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

### Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

**Explosion data** 

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### TO A COLUMN TO THE PARTY OF THE

### Personal precautions, protective equipment and emergency procedures

Personal precautions

Remove all sources of ignition. Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing.

Wash thoroughly after handling.

Environmental precautions

**Environmental precautions** 

Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

### THE MADENIC AND STORAGE

### Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Store locked up.

Incompatible materials

Strong oxidizing agents

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION AND A LARGE

#### Control parameters

Exposure Guidelines

Exposure Guidelines Chemical Name	. ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC 14807-96-6	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m³ TWA: 2 mg/m³ containing no Asbestos and <1% Quartz respirable dust
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

### Appropriate engineering controls

### 21127 - 765-1188 NAPA THREAD SEALANT W/PTFE (PTX80632) 4 FL.OZ

**Engineering Controls** 

Showers

Eyewash stations Ventilation systems

### Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

### 9 PHYSICAL AND THE MICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state **Appearance** 

Paste White Alcoholic

Odor **Odor threshold** 

No information available

Property

Values

Remarks • Method

рH Melting point / freezing point No information available No information available

No information available

Boiling point / boiling range

82 °C / 180 °F

Flash point Evaporation rate 23 °C / 74 °F

Tag Closed Cup Butyl acetate = 1

Air = 1

Flammability (solid, gas)

Flammability Limit in Air

Upper flammability limit:

12.7% 2.3%

< 1

Lower flammability limit: Vapor pressure

33 mm Hg @ 68°F

Vapor density Relative density >1 1.06-1.10 Partially soluble

Water solubility Solubility in other solvents Partition coefficient

No information available No information available

Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity **Explosive properties** 

No information available No information available No information available No information available

No information available

No information available

Oxidizing properties Other Information

Softening point Molecular weight **VOC Content (%)** 

No information available No information available

36.7%

No information available No information available

### 10 STABILITY AND REAGTIMITY AND REAGTIMITY

Reactivity

**Bulk density** 

Density

No data available

# 21127 - 765-1188 NAPA THREAD SEALANT W/PTFE (PTX80632) 4 FL.OZ

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

**Conditions to avoid** 

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

**Hazardous Decomposition Products** 

Carbon oxides

Fluorides

### PRODUCTION OF THE PRODUCTION O

### Information on likely routes of exposure

Inhalation

Harmful by inhalation.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg(Rabbit)	= 72600 mg/m³ (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg(Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

### Information on toxicological effects

**Symptoms** 

No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity	The table bel	<u>ow indicates whether each</u>	agency has listed any ing	
Chemical Name	ACGIH	IARC	NTP	OSHA
TALC 14807-96-6	-	Group 3	-	<b>.</b>
ETHANOL 64-17-5	А3	Group 1	Known	X
2-PROPANOL 67-63-0	-	Group 1	-	X
TITANIUM DIOXIDE 13463-67-7	••	Group 2B	-	X
POLYTETRAFLUOROETHY LENE 9002-84-0	in the state of th	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Chronic toxicity** 

May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

**Target Organ Effects** 

Blood, Central nervous system, Central Vascular System (CVS), Eyes, Gastrointestinal

tract (GI), Liver, Lungs, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document  $\,$  .

ATEmix (oral)

1811 mg/kg

ATEmix (dermal)

6521 mg/kg

ATEmix (inhalation-dust/mist)

11.7 mg/l

### 12 ECOLOGICAL NEORMATION

### **Ecotoxicity**

35,44605% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
TALC 14807-96-6	*	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
ETHANOL 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
2-PROPANOL 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	11130: 96 h Pimephales promelas mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
METHANOL 67-56-1	-	28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static	<del>-</del>

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient
ETHANOL 64-17-5	-0.32
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77

#### Other adverse effects

No information available

### MENDISPOSAL CONSIDERATIONS - PER PROPERTY - PROPERTY -

### Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not reuse container.

**US EPA Waste Number** 

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHANOL	_	Included in waste stream:	-	U154
67-56-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL	· Toxic
64-17-5	Ignitable
2-PROPANOL	Toxic
67-63-0	Ignitable
METHANOL	Toxic
67-56-1	Ignitable

### A TRANSPORT IN CIRMARION CONTRACTOR OF THE PROPERTY OF THE PRO

DOT

UN/ID no

1133

Proper shipping name:

Adhesives, Limited Quantity (LQ)

**Hazard Class** 

**Packing Group** 

Ш

**Emergency Response Guide** 

128

Number

IATA

UN/ID no

ID 8000

Proper shipping name:

Consumer commodity

**Hazard Class** 

9

**ERG Code** 

9L

IMDG

UN/ID no

Proper shipping name:

Adhesives, Limited Quantity (LQ)

**Hazard Class** 

**Packing Group** 

111

**EmS-No** 

F-E, S-D

### MERECUEATORY INFORMATION

International Inventories

Complies **TSCA** DSL/NDSL Complies Not Listed. **EINECS/ELINCS** Not Listed. **ENCS** Complies **IECSC** 

## 21127 - 765-1188 NAPA THREAD SEALANT W/PTFE (PTX80632) 4 FL.OZ

KECLCompliesPICCSCompliesAICSComplies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHANOL - 67-56-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHANOL	5000 lb		RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ

### **US State Regulations**

### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen Developmental
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
METHANOL - 67-56-1	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TALC 14807-96-6	Х	X	Х
ETHANOL 64-17-5	Х	X	X
2-PROPANOL 67-63-0	Х	X	X

# 21127 - 765-1188 NAPA THREAD SEALANT W/PTFE (PTX80632) 4 FL.OZ

TITANIUM DIOXIDE 13463-67-7	Х	Х	X
WATER 7732-18-5	-	-	X
METHANOL 67-56-1	Х	Х	X
POLYTETRAFLUOROETHYLENE 9002-84-0	•	-	X
METHYL ISOBUTYL KETONE 108-10-1	Х	Х	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA HMIS Health hazards 2 Health hazards 2

Flammability 3 Flammability 3

Instability 0

Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 

24-Apr-2015

**Disclaimer** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**