

Material Safety Data Sheet

Company:

CGW - Camel Grinding Wheels, Inc. 7525 N. Oak Park Ave, Niles, IL. 60714 tel.800-447-4248 - fax.800-447-3731

Product Type:

Aluminum Oxide, Silicon Carbide, Alumina-Zirconia

1)Coated onto a backing of cloth, paper or vulcanized fibre using hide glue or phenolic resin.
2) Bonded with phenolic resin arid reinforced with woven fiberglass mesh.

Common Name or Specification:

Coated Abrasive Products, Resinoid Bonded Abrasive Flapwheels

Grinding Discs and Cut-Off Wheels

Date of issue: January 01, 2015

SECTION II COMPOSITION MAY CONTAIN ONE OR MORE OF THE FOLLOWING:

CHEMICA L NAME	COMMON NAME	OSHAREG(Y/N)	CAS #	OSHA PERMISSIV E EXPOSURE LIMI	ACHIHTLV	CARCINOGE N (Y/N)
AL O	Aluminum Oxíde	Υ	1344-28-1	15mg/M³	10mg/M³	N
AL ₂ O ₃	Silicon Carbide	Ÿ	409-21-2	15mg/M³	10mg/M³	N
SIC	Alumina Zirconia	·	1314-23-4	15mg/M³	10mg/M³	N
AL ₂ O ₃ -ZrO ₂		<u> </u>	15096-52-3	N/A	N/A	N
NA ₃ AIF ₆	Cryolite		14075-53-7	N/A	N/A	N
KBF4	Potassium Floroborat			N/A	N/A	N
luminum Patassium Fluorid	Cured Phenolic		60304-36-1		N/A	N
CaO	Caldium Oxide		1305-78-8	2mg/M³		
Zn(C ₁₈ H ₃ :O ₂) ₂	Zinc Stearate		557-05-1	N/A	10mg/M³	N

SECTION III PHYSICAL AND CHEMICAL DATA

DOLLING BOINT:	N/A	MELTING POINT:		N/A	SPECIFIC GRAVITY: N/A
BOILING POINT:		PERCENT VOLAT		N/A	VAPOR DENSITY: N/A
VAPOR PRESSURE:	N/A	SOLUBILITY IN W		NO	SOLUBILITY IN ALCOHOL: N/A
EVAPORATION RATE:	N/A	APPEARANCE AND C			DDOR:
			1) Paper, clo	th or fibre	e coated with abrasive grain-No odor ed discs and wheels-No odor

SECTION IV FIRE AND EXPLOSION HAZARD DATA

	FLASH POINT: N/A	METHOD US	SED: N/A	FLAMMABLE ELEMENTS, LEV: N/A UEL: N/A
١	EXTINGUISHING MEDIA:	Any proper fire-fighting material can be used.		
				sin binder will burn or decompose,use respiratory protection.
	SPECIAL FIRE FIGHTING PR		Dadking G To	
	EXPLOSION POTENTIAL:	N/A		

NFPA RATIN	IGS
Health	1
Flammability	0
Reactivity	0
Personal protection	С

SECTION V HEALTH, FIRST AID AND MEDICAL DATA

ACUTE & CHRONIC HEALTH EFFECTS & EFFECTS OF OVEREXPOSURE	FIRST AID & MEDICAL INFORMATION
ACUTE - MAY CAUSE COUGHING SHORT- NESS OF BREATH. CHRONIC-MAY AFFECT BREATHING CAPACITY	REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION AS NEEDED. OBTAIN FIRST AID OR MEDICAL ASSISTANCE.
NO KNOWN ADVERSE EFFECTS BUT INGESTION NOT RECOMMENDED.	OBTAIN FIRST AID OR MEDICAL ASSISTANCE, IF NEEDED.
NOT ABSORBED THROUGH SKIN; MAY CAUSE ABRASIONS.	OBTAIN FIRST AID OR MEDICAL ASSISTANCE, IF NEEDED.
DUST MAY IRRITATE EYES	WASH WITH LARGE AMOUNT OF WATER. OBTAIN MEDICAL ASSISTANCE, IF NEEDED.
DURING USE ON SOME MATERIALS ELE- VATED SOUND LEVELS MAY BE CREATED WHICH AFFECT HEARING.	OBTAIN MEDICAL ASSISTANCE.
	EFFECTS OF OVEREXPOSURE ACUTE - MAY CAUSE COUGHING SHORT- NESS OF BREATH. CHRONIC-MAY AFFECT BREATHING CAPACITY NO KNOWN ADVERSE EFFECTS BUT INGESTION NOT RECOMMENDED. NOT ABSORBED THROUGH SKIN; MAY CAUSE ABRASIONS. DUST MAY IRRITATE EYES DURING USE ON SOME MATERIALS ELE- VATED SOUND LEVELS MAY BE CREATED

SECTION VI CORROSIVITY AND REACTIVITY DATA

STABILITY: UNSTABLE STABLE POLYMERIZATION: MAY OCCUR WILL NOT OCCUR MINCOMPATIBILITY: (MATERIAL TO AVOID) N/A NONE CONDITIONS TO BE AVOIDED: NONE

DECOMPOSITION PRODUCTS: In use, dust and decomposing resin system fumes are generated. In most cases, the material removed from the work piece will be significantly greater than the coated abrasive product components.

SECTION VII STORAGE, HANDLING AND USE PROCEDURES

NORMAL STORAGE AND HANDING: Handle with adequate ventilation. See OSHA 29CFR1910.94 (Ventilation) and

OSHA 29CFR1910.1000 (Air Contaminates)

NORMAL USE: Handle with adequate ventilation. See OSHA 29CFR1910.94 (Ventilation) and

OSHA 290FR1910.1000 (Air Contaminates) OSHA CRF1910.213 (P) Sanding

Machines.

STEPS TO BETAKEN IN CASE OF LEAKS OR SPILLS: Normal clean up procedures. Vacuum dust

WASTE DISPOSAL METHOD: Standard landfill methods consistent with applicable Federal, State and Local Laws

SECTION VIII PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	(SPECIFY TYPE) As needed, approved dust respirator OSHA 24 CFR1910-134. NOISH/MSHA			
VENTILATION: LOCAL:	Recommended			
	MECHANICAL (GENERAL): Recommended			
PROTECTIVE GLOVES:	Leather gloves as desired by user.			
EYE PROTECTION:	Recommend-OSHA 29CFR1910.133 (Face & Eye Protection)			
OTHER EQUIPMENT:	As needed, hearing protection - OSHA 29CFR1 910.215 (Hearing Protection) All			
	recommendations as per ANSI 37.1 Safety Guidelines.			
MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT THAT HAS BEEN IN				
CONTACT WITH THIS MATERIAL: No special precautions necessary.				

In compliance with Federal OSHA Standard 29CFR 1910. 1200 contained herein are Material Safety Data Sheets (MSDS) for the entire product line currently offered by **Camel Grinding Wheel.**; for coated abrasives and bonded abrasives.

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, **Camel Grinding Wheel** makes no warranty with respect to the accuracy of the information for the suitability of the recommendations and assumes no liability to any user thereof.

Please contact our Applications Department at 800-647-5994 if you have further questions or comments.

Sincerely,

Applications Department CGW - Camel Grinding Wheels, Inc.