# SAFETY DATA SHEET

Version 1

Revision Date 27-Mar-2015

### A PIDENTIFICATION

Product identifier

**Product Name** 

765-4674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

Other means of identification

**Product Code Synonyms** 

21201 None

Recommended use of the chemical and restrictions on use

**Recommended Use** 

Lubricant

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Distributor

ITW Permatex

ITW Permatex Canada

10 Columbus Blvd.

35 Brownridge Road, Unit 1

Hartford, CT 06106 USA

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

**Company Phone Number** 

1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

## 2. HAZARDS IDENTIFICATION.

#### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral

Category 4

#### Label elements

**Emergency Overview** 

Warning

Harmful if swallowed



Appearance Silver

Physical state Paste

Odor Mild petroleum odor

**Precautionary Statements - Prevention** 

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

**Precautionary Statements - Response** 

Get medical advice/attention if you feel unwell

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

**Precautionary Statements - Storage** 

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal** 

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I Harmful to aquatic life with long lasting effects

Unknown acute toxicity

19.23275% of the mixture consists of ingredient(s) of unknown toxicity

### ergombos monnieormationeoningredienes

#### substance

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30 - 60	*
CALCIUM OXIDE	1305-78-8	10 - 30	*
GRAPHITE	7782-42-5	10 - 30	*
ALUMINIUM POWDER	7429-90-5	5 - 10	*
MINERAL OIL	8042-47-5	3 - 7	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

ENTER SERVICE REPORT OF THE PROPERTY OF THE PR

#### 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

Skin contact

IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** 

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES WERE AND THE FIRE OF THE PROPERTY OF

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact

Sensitivity to Static Discharge

None.

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# BELLEVILLE OF ACOUNTY AND ACTION OF THE ACTI

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions** 

Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

#### PARTICIAN DENGANDESTORAGE PARTICIPATION OF THE PART

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials

Strong oxidizing agents, Acids, Alkali, Amines

#### RMENTEROS DE ETCONORCO ESTADA CONTRA ESTADO DE CONTRA ESTADO DE CONTRA ESTADA ESTADA CONTRA ESTADA CONTRA ESTADA ESTADA ESTADA ESTADA ESTADA CONTRA ESTADA E

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM OXIDE	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m³	IDLH: 25 mg/m <sup>3</sup>
1305-78-8	_	(vacated) TWA: 5 mg/m³ not in	TWA: 2 mg/m <sup>3</sup>
		effect as a result of reconsideration	
GRAPHITE	TWA: 2 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust synthetic	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	all forms except graphite fibers	TWA: 5 mg/m³ respirable fraction	TWA: 2.5 mg/m³ natural respirable
		synthetic	dust
		(vacated) TWA: 2.5 mg/m³	
		respirable dust natural	
		(vacated) TWA: 10 mg/m³ total dust	
		synthetic	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction synthetic	<u>_</u>
		TWA: 15 mppcf natural	<u> </u>
ALUMINIUM POWDER	TWA: 1 mg/m3 respirable fraction	TWA: 15 mg/m³ total dust	TWA: 5 mg/m³ Al
7429-90-5		TWA: 5 mg/m³ respirable fraction	
		(vacated) TWA: 5 mg/m³ Al	
		Aluminum	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

**Engineering Controls** 

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

#### 

Information on basic physical and chemical properties

Physical state

Paste

Remarks • Method

Tag Closed Cup

Butyl acetate = 1

Air = 1

#### 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

**Appearance** 

Odor **Odor threshold**  Silver

Mild petroleum odor No information available

**Property** 

pН Melting point / freezing point Boiling point / boiling range

Values

No information available No information available No information available Not

determined

Flash point **Evaporation rate** 

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Lower flammability limit:

Vapor pressure Vapor density Relative density Water solubility

Solubility in other solvents Partition coefficient Autoignition temperature **Decomposition temperature** Kinematic viscosity Dynamic viscosity

**Explosive properties** Oxidizing properties

< 1 No information available

> 93 °C / > 200 °F

No information available No information available

<5 mm Hg >1

1.17 Negligible

No information available No information available

Other Information

Softening point Molecular weight VOC Content (%)

Density **Bulk density**  No information available No information available

0

No information available No information available

# 10 STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

**Conditions to avoid** 

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Alkali, Amines

**Hazardous Decomposition Products** 

Carbon oxides

#### HITOXICOLOGICALINEORMATION:

Information on likely routes of exposure

# 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM OXIDE 1305-78-8	= 500 mg/kg (Rat)	•	-
MINERAL OIL 8042-47-5	> 5000 mg/kg (Rat)	-	-

#### Information on toxicological effects

**Symptoms** 

No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.Chemical NameACGIHIARCNTPOSHADISTILLATESA2Group 1-X

(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5

TIED HEAVY

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Target Organ Effects** 

Central Vascular System (CVS), Eyes, Respiratory system, Skin.

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

1978 mg/kg

ATEmix (inhalation-vapor)

32255 mg/l

#### 124ECOLOGICALINFORWATION

#### **Ecotoxicity**

32,42995% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
CALCIUM OXIDE 1305-78-8	<del>-</del>	1070: 96 h Cyprinus carpio mg/L LC50 static	· · · <b>-</b>
MINERAL OIL 8042-47-5	*	10000: 96 h Lepomis macrochirus mg/L LC50	-

#### Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

### 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

**Mobility** 

No information available.

Chemical Name	Partition coefficient
MINERAL OIL	>6
8042-47-5	

#### Other adverse effects

No information available

## MOLDISPOSAL CONSIDERATIONS OF THE PARTIES OF THE PA

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

**US EPA Waste Number** 

Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
CALCIUM OXIDE 1305-78-8	Corrosive
ALUMINIUM POWDER 7429-90-5	Ignitable powder

#### A TRANSPORT NEORMATION CONTRACTOR OF THE PROPERTY OF THE PROPE

DOT

Proper shipping name:

Not regulated

Proper shipping name:

Not regulated

**IMDG** 

Proper shipping name:

Not regulated

# EN SERECULATION VINEORNATION OF THE SERVICE OF THE

**International Inventories** 

**TSCA** 

Complies

DSL/NDSL

Complies

**EINECS/ELINCS** 

Complies

**ENCS** 

Natural substance

**IECSC** 

Complies

**KECL** 

Complies

**PICCS** 

**AICS** 

Complies Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

# 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ALUMINIUM POWDER - 7429-90-5	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)** 

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

#### **US State Regulations**

#### California Proposition 65

This product does not contain any Proposition 65 chemicals

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CALCIUM OXIDE 1305-78-8	X	Х	Х
GRAPHITE 7782-42-5	X	Х	X
ALUMINIUM POWDER 7429-90-5	X	Х	Х
MINERAL OIL 8012-95-1	X	X	Х
COPPER 7440-50-8	X	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 1 Flammability 1 Instability 0 HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

**Revision Date** 

27-Mar-2015

**Disclaimer** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**