



# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/01/2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : PEAK RV and Marine Antifreeze -50 F Burst  
Product code : PKR0A1; PKR0A3

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Anti-freezing agent

#### 1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC  
3100 Sanders Road  
Northbrook, IL 60062 - USA  
T (847) 559-2000  
[www.oldworldind.com](http://www.oldworldind.com)

#### 1.4. Emergency telephone number

Emergency number : 800 424 9300; 00 1 703 527 3887 (International)  
Chemtrec

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Not classified

#### 2.2. Label elements

##### GHS-US labelling

Signal word (GHS-US) : None  
Hazard statements (GHS-US) : None  
Precautionary statements (GHS-US) : None

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
water	(CAS-No.) 7732-18-5	70 - 75	Not classified
propylene glycol	(CAS-No.) 57-55-6	25 - 30	Not classified

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell.  
First-aid measures after skin contact : Not expected to present a significant hazard under anticipated conditions of normal use.  
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth. Obtain emergency medical attention.

# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Excessive ingestion may cause central nervous system effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Reactivity : Stable.

### 5.3. Special protective equipment and precautions for fire-fighters

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain released product, pump into suitable containers.
Methods for cleaning up	: Notify authorities if product enters sewers or public waters. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

propylene glycol (57-55-6)	
Not applicable	
water (7732-18-5)	
Not applicable	

### 8.2. Appropriate engineering controls

No additional information available

# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Face shield. Protective goggles.

#### Hand protection:

Not required for normal conditions of use

#### Eye protection:

Chemical goggles or face shield

#### Respiratory protection:

If exposed to levels above exposure limits wear appropriate respiratory protection.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Red
Odor	: Odorless
Odor threshold	: No data available
Relative evaporation rate (butylacetate=1)	: Slight
Melting point	: -12 °C (9 °F)
Freezing point	: No data available
Boiling point	: 102 °C (216 °F)
Flash point	: None. Percentage of water is above 20%.
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.01 kPa (<0.1 mm Hg)
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 1.02
Density	: 1.02 kg/l (8.5 lbs/gal)
Solubility	: Water: Complete
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Explosive limits	: Not determined.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable.

### 10.2. Chemical stability

Stable.

# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

propylene glycol (57-55-6)	
LD50 oral rat	20000 mg/kg (Rat; Experimental value)
LD50 dermal rat	22500 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	20800 mg/kg (Rabbit; Experimental value)
ATE US (oral)	20000 mg/kg bodyweight
ATE US (dermal)	20800 mg/kg bodyweight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Contact during a long period may cause light irritation.

Symptoms/effects after eye contact : May cause slight irritation.

Symptoms/effects after ingestion : Excessive ingestion may cause central nervous system effects.

## SECTION 12: Ecological information

### 12.1. Toxicity

propylene glycol (57-55-6)	
EC50 Daphnia 1	34,400.00 mg/l (EC50; 48 h)
LC50 fish 2	51,600.00 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss)

### 12.2. Persistence and degradability

propylene glycol (57-55-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in soil.
Biochemical oxygen demand (BOD)	0.96 - 1.08 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.63 g O <sub>2</sub> /g substance
ThOD	1.69 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.57

### 12.3. Bioaccumulative potential

# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

propylene glycol (57-55-6)	
Log Pow	-1.41 - -0.30 (-0.92; Experimental value; -1.07; Experimental value; Equivalent or similar to OECD 107; 20.5 °C)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

propylene glycol (57-55-6)	
Surface tension	0.04 N/m (25 °C)

### 12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Not regulated

### Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

### Transport by sea

In accordance with IMDG / IMO

Not regulated

### Air transport

In accordance with IATA / ICAO

Not regulated

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

PEAK RV and Marine Antifreeze -50 F Burst	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. International regulations

#### CANADA

PEAK RV and Marine Antifreeze -50 F Burst	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

### EU-Regulations

No additional information available

### National regulations

# PEAK RV and Marine Antifreeze -50 F Burst

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### PEAK RV and Marine Antifreeze -50 F Burst

DSL (Canada): The intentional ingredients of this product are listed  
ECL (South Korea): The intentional ingredients of this product are listed.  
EINECS (Europe): The intentional ingredients of this product are listed  
ENCS (Japan): The intentional ingredients of this product are listed

### 15.3. US State regulations

#### propylene glycol (57-55-6)

U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Revision date : 03/01/2018

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.  
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



#### Hazard Rating

Health : 0 Minimal Hazard - No significant risk to health  
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 °F (93 °C). (Class IIIB)  
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS GHS US (GHS HazCom 2012) OWI

*Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.*