



1 Identification

- Product identifier
- Trade name: **39523 Rubberized Undercoating**
- Article number: 39523
- Application of the substance / the mixture Coating
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- Information department:
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 39523 Rubberized Undercoating

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

toluene

· Hazard statements

H222 *Extremely flammable aerosol.*

H280 *Contains gas under pressure; may explode if heated.*

H315 *Causes skin irritation.*

H361 *Suspected of damaging fertility or the unborn child.*

H336 *May cause drowsiness or dizziness.*

H373 *May cause damage to organs through prolonged or repeated exposure.*

H304 *May be fatal if swallowed and enters airways.*

· Precautionary statements

P201 *Obtain special instructions before use.*

P202 *Do not handle until all safety precautions have been read and understood.*

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

P211 *Do not spray on an open flame or other ignition source.*

P251 *Pressurized container: Do not pierce or burn, even after use.*

P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*

P264 *Wash thoroughly after handling.*

P271 *Use only outdoors or in a well-ventilated area.*

P280 *Wear protective gloves/protective clothing/eye protection/face protection.*

P301+P310 *If swallowed: Immediately call a poison center/doctor.*

P321 *Specific treatment (see on this label).*

P331 *Do NOT induce vomiting.*

P302+P352 *If on skin: Wash with plenty of water.*

P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P308+P313 *IF exposed or concerned: Get medical advice/attention.*

P312 *Call a poison center/doctor if you feel unwell.*

P314 *Get medical advice/attention if you feel unwell.*

P362+P364 *Take off contaminated clothing and wash it before reuse.*

P332+P313 *If skin irritation occurs: Get medical advice/attention.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P405 *Store locked up.*

P410+P403 *Protect from sunlight. Store in a well-ventilated place.*

P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 4

Reactivity = 3

(Contd. on page 3)



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39523 Rubberized Undercoating

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT: Not applicable.**
- **vPvB: Not applicable.**

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· Dangerous components:		
108-88-3	toluene	40-60%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
7727-43-7	barium sulphate, natural	10-13%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

108-88-3	toluene	67 ppm
7727-43-7	barium sulphate, natural	15 mg/m ³
67-56-1	methanol	530 ppm
1333-86-4	Carbon black	9 mg/m ³

· **PAC-2:**

108-88-3	toluene	560 ppm
7727-43-7	barium sulphate, natural	170 mg/m ³
67-56-1	methanol	2,100 ppm
1333-86-4	Carbon black	99 mg/m ³

· **PAC-3:**

108-88-3	toluene	3700* ppm
7727-43-7	barium sulphate, natural	990 mg/m ³
67-56-1	methanol	7200* ppm
1333-86-4	Carbon black	590 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 4)

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

7727-43-7 barium sulphate, natural

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E

- **Ingredients with biological limit values:**

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 6)

Trade name: 39523 Rubberized Undercoating

(Contd. of page 5)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	<i>Aerosol</i>
· Color:	<i>According to product specification</i>
· Odor:	<i>Characteristic</i>
· Odor threshold:	<i>Not determined.</i>

· **pH-value:** *Not determined.*

· **Change in condition**

· Melting point/Melting range:	<i>Undetermined.</i>
· Boiling point/Boiling range:	<i>110 °C</i>

· **Flash point:** *-103 °C*

· **Flammability (solid, gaseous):** *Not applicable.*

· **Ignition temperature:** *535 °C*

· **Decomposition temperature:** *Not determined.*

· **Auto igniting:** *Product is not selfigniting.*

· **Danger of explosion:** *In use, may form flammable/explosive vapour-air mixture.*

(Contd. on page 7)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 6)

· Explosion limits:	
Lower:	1.2 Vol %
Upper:	9.5 Vol %
· Vapor pressure at 20 °C:	29 hPa
· Density at 20 °C:	1.05826 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	66.3 %
Water:	0.0 %
VOC content:	66.28 %
	701.8 g/l / 5.86 lb/gl
· Solids content:	34.5 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.

(Contd. on page 8)



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39523 Rubberized Undercoating

(Contd. of page 7)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
1333-86-4	Carbon black	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1950
· UN proper shipping name	
· DOT	Aerosols, flammable

(Contd. on page 9)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 8)

· **ADR** 1950 Aerosols
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
 · **Label** 2.1

· **ADR**



· **Class** 2 5F Gases
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
 · **Label** 2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

· **EMS Number:**

· **Stowage Code**

Warning: Gases

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
 Category A. For AEROSOLS with a capacity above 1 litre:
 Category B. For WASTE AEROSOLS: Category C, Clear of living
 quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for
 division 1.4. For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2. For
 WASTE AEROSOLS: Segregation as for the appropriate subdivision
 of class 2.

· **Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 10)



Printing date 03/14/2018

Reviewed on 06/20/2017

Trade name: 39523 Rubberized Undercoating

(Contd. of page 9)

· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

· ADR	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):	
108-88-3	toluene
7727-43-7	barium sulphate, natural
67-56-1	methanol
· TSCA (Toxic Substances Control Act):	
108-88-3	toluene
7727-43-7	barium sulphate, natural
69430-35-9	Alicyclic hydrocarbon resin
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer
66070-58-4	Styrene-Ethylene/Butylene-Styrene block Copolymer
67-56-1	methanol
1333-86-4	Carbon black
8042-47-5	White Mineral oil
6683-19-8	Tertrakis(methylene(3,5-di(tert)-butyl-4-hydroxyhydrocinnamate)) methane
84633-54-5	Pentaerythritol tris tri ester with 3-(3,5-di(tert)-butyl-4-hydroxyphenyl)propionic acid
7732-18-5	water
· TSCA new (21st Century Act) (Substances not listed)	
68476-86-8	Petroleum gases, liquefied, sweetened
· Proposition 65	
· Chemicals known to cause cancer:	
1333-86-4	Carbon black

(Contd. on page 11)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

1333-86-4 Carbon black

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

67-56-1 methanol

1333-86-4 Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 12)



Trade name: 39523 Rubberized Undercoating

(Contd. of page 11)

- P321 Specific treatment (see on this label).
 - P331 Do NOT induce vomiting.
 - P302+P352 If on skin: Wash with plenty of water.
 - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - P308+P313 IF exposed or concerned: Get medical advice/attention.
 - P312 Call a poison center/doctor if you feel unwell.
 - P314 Get medical advice/attention if you feel unwell.
 - P362+P364 Take off contaminated clothing and wash it before reuse.
 - P332+P313 If skin irritation occurs: Get medical advice/attention.
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 - P405 Store locked up.
 - P410+P403 Protect from sunlight. Store in a well-ventilated place.
 - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Rita Joiner (rjoiner@semproducts.com)
- **Date of preparation / last revision** 03/14/2018 / 8

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

- *** Data compared to the previous version altered.**