

Safety Data Sheet

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:

08-0531-7

Version Number:

16.00

Issue Date:

05/12/15

Supercedes Date:

06/01/12

SECTION 1: Identification

1.1. Product identifier

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581

LB-K000-1071-0, 41-0003-7951-5, 41-3701-2175-2, 60-4550-2996-1, 60-4550-5472-0, 60-4550-5560-2, 60-4550-5843-2, 60-9800-3122-7

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Adhesive

1.3. Supplier's details

MANUFACTURER:

DIVISION:

3M Automotive Aftermarket

ADDRESS:

3M Center, St. Paul, MN 55144-1000, USA

Telephone:

1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (central nervous system): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |





Hazard Statements

Highly flammable liquid and vapor.

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May damage fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs: sensory organs

Causes damage to organs through prolonged or repeated exposure: nervous system sensory organs |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

22% of the mixture consists of ingredients of unknown acute dermal toxicity.

41% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

	C.A.S. No.	% by Wt
Ingredient	Trade Secret*	10 - 30 Trade Secret *
Phenolic Polymer, NJTS# 04499600-6305	9010-98-4	10 - 30 Trade Secret *
Polychloroprene	78-93-3	10 - 30 Trade Secret *
Methyl Ethyl Ketone	110-54-3	4 - 15 Trade Secret *
Hexane	I	5 - 10 Trade Secret *
Toluene	108-88-3	3 - 7 Trade Secret *
Magnesium Oxide	1309-48-4	1 - 7 Trade Secret *
Methylcyclopentane	96-37-7	1 - 7 Trade Secret *
Heptane	142-82-5	1 - 5 Trade Secret *
3-Methylpentane	96-14-0	1 - 5 Trade Secret *
2-Methylpentane	107-83-5	1 - 5 Trade Secret *
Xylene	1330-20-7	1 - 5 Trade Secret *
	100-41-4	0.1 - 1.0 Trade Secret *
Ethylbenzene	1333-86-4	< 0.5 Trade Secret *
Carbon Black	50-00-0	< 0.05 Trade Secret *
Formaldehyde	71-43-2	< 0.05 Trade Secret *
Benzene	7,1-43-2	

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop,

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only

non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

r the component.	C.A.S. No.	Agency	Limit type	Additional Comments
ngredient	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal
Ethylbenzene	100-41-4	ACGIII		carcin.
	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
Ethylbenzene	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	<u> </u>
Ethylbenzene	107-83-5	ACGIH	TWA:500 ppm;STEL:1000	
2-Methylpentane	107-05-5	1100111	ppm	27.1.
	108-88-3	CMRG	STEL:75 ppm	Skin Notation
<u> Foluene</u>	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	- large
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
Toluene	100 00 3			carcin
- M	110-54-3	ACGIH	TWA:50 ppm	Skin Notation
Hexane	110-54-3	OSHA	TWA:1800 mg/m3(500 ppm)	A A A T A A Language human
Hexane	1309-48-4	ACGIH	TWA(inhalable fraction):10	A4: Not class. as human
Magnesium Oxide	1307-40 1		mg/m3	carcin
Magnesium Oxide	1309-48-4	OSHA	TWA(as total particulates):15	
	1,50, 10	1	mg/m3	
N7 1	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	A4: Not class, as huma
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	carcin
Xylene				carem
V-lane	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	A3: Confirmed animal
Xylene	1333-86-4	ACGIH	TWA(inhalable fraction):3	
Carbon Black			mg/m3	carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Carbon Black	1333-86-4	CMRG	TWA:0.5 mg/m3	<u> </u>
	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppr	<u>n</u>
Heptane	50-00-0	CMRG	TWA:0.5 ppm	29 CFR 1910.1048
Formaldehyde	50-00-0	OSHA	TWA:0.75 ppm;STEL:2 ppm	A2: Suspected human
Formaldehyde	50-00-0	ACGIH	CEIL:0.3 ppm	carcin., Sensitizer
Formaldehyde				29 CFR 1910.1028
	71-43-2	OSHA	TWA:1 ppm;TWA:10	29 CFR 1910.1020
Benzene			ppm;STEL:5 ppm;CEIL:25	
			ppm	

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

Benzene	71-43-2	ACGIH	TWA:0.5 ppm;STEL:2.5 ppm A1: Con	firmed human
Methyl Ethyl Ketone	78-93-3	ACGIH		Skin Notation
Methyl Ethyl Ketone	78-93-3	OSHA	TWA:590 mg/m3(200 ppm)	
3-Methylpentane	96-14-0	ACGIH	TWA:500 ppm;STEL:1000	
ACGIH: American Conference of (nl Hygienists	ppm	

AlHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

Gloves made from the following material(s) are recommended: Fluoroelastomer Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:

Odor, Color, Grade:

Black. Solvent odor.

Odor threshold

No Data Available

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

рH

Melting point

Boiling Point

Flash Point

Evaporation rate

Flammability (solid, gas) Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

Density

Specific Gravity

Solubility in Water

Solubility- non-water Partition coefficient: n-octanol/ water

Autoignition temperature

Decomposition temperature

Viscosity

Hazardous Air Pollutants

Volatile Organic Compounds

Volatile Organic Compounds

Percent volatile

VOC Less H2O & Exempt Solvents

Not Applicable

No Data Available

148 - 189 °F

-6.00 °F [Test Method: Tagliabue Closed Cup]

>=3.60 [Ref Std: ETHER=1]

Not Applicable

1.00 % volume

11.50 % volume

120.0000 mmHg [@ 68 °F]

3.00 [Ref Std: AIR=1]

0.90 g/ml

0.90 [Ref Std: WATER=1]

Slight (less than 10%)

No Data Available

No Data Available

No Data Available

No Data Available

7,500 - 9,500 centipoise

0.57 lb HAPS/lb solids [Test Method: Calculated]

558 g/l [Test Method: calculated SCAQMD rule 443.1]

61.5 % weight [Test Method: calculated per CARB title 2]

60.7 % weight

560 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Carbon monoxide

Carbon dioxide

Toxic Vapor, Gas, Particulate

Condition

Not Specified

Not Specified

Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the comea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient Benzene Benzene	CAS No. 71-43-2 71-43-2	Class Description Grp. 1: Carcinogenic to humans Known human carcinogen	The rest of the re
	171 43-2	Known numan carcinogen	National Toxicology Program Carcinogens

[Daugene	71-43-2	Cancer hazard	OSHA Carcinogens
Benzene Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Formaldehyde	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Formaldehyde	50-00-0	Known human carcinogen	National Toxicology Program Carcinogens
Formaldehyde	50-00-0	Cancer hazard	OSHA Carcinogens
FOI III MI GERY GE			

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

À	cute	Toxicity
_	Lut	TOVICIO

cute Toxicity	Route	Species	Value Value 5 5 000 mg/kg
ovame Overali product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE > 50 mg/l
grotan product	Vapor(4 hr)		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-	Rat	LC50 34.5 mg/l
Methyl Emyl Retone	Vapor (4		
	hours)		T D CO 2 122 (les
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-	Rat	LC50 170 mg/l
itezuno	Vapor (4		
	hours)		LD50 > 28,700 mg/kg
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg
Phenolic Polymer, NJTS# 04499600-6305	Ingestion	 	LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Dermal		LD50 > 20,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
Heptane	Dermal	Rabbit	LC50 103 mg/l
Heptane	Inhalation-	Rat	LC30 103 mg/1
	Vapor (4		
	hours)	- B-4	LD50 > 15,000 mg/kg
Heptane	Ingestion	Rat	LD50 > 5,000 mg/kg
Methylcyclopentane	Ingestion	Rat	LD50 12,000 mg/kg
Toluene	Dermal	Rat	LC50 30 mg/l
Toluene	Inhalation-	Rat	1C30 30 mg/l
	Vapor (4		
	hours)	Rat	LD50 5,550 mg/kg
Toluene	Ingestion	Rat	LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Dermal		LC50 estimated to be > 50 mg/l
2-Methylpentane	Inhalation-		BC30 (attitude to a 1)
	Vapor		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Ingestion Dermal	 	LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Inhalation-	+	LC50 estimated to be > 50 mg/l
3-Methylpentane	Vapor		
	Ingestion		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Dermal	Professio	1 0 000 € 000 mg/kg
Magnesium Oxide	Dellia	nal	
		judgeme	
	1	nt	
	Ingestion	Rat	LD50 3,870 mg/kg
Magnesium Oxide	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-	Rat	LC50 29 mg/l
Xylene	Vapor (4		
	hours)		
	Ingestion	Rat	LD50 3,523 mg/kg
Xylene	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-		LC50 17.4 mg/l
Ethylbenzene	Vapor (4		
	hours)	1	
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

Formaldehyde Formaldehyde	Dermal Inhalation- Gas (4	Rabbit Rat	LD50 270 mg/kg LC50 470 ppm
Formaldehyde ATE = acute toxicity estimate	hours) Ingestion	Rat	LD50 800 mg/kg

Skin Corrosion/Irritation

Name	Species	Value
Methyl Ethyl Ketone		
Hexane	Rabbit	Minimal irritation
Texage	Human	Mild irritant
	and	
Polychloroprene	animal	
Heptane ————————————————————————————————————	Human	No significant irritation
Methylcyclopentane	H _u man	Mild irritant
wietnyteyetopentane	similar	Minimal irritation
	сотроип	
Toluene	ds	
	Rabbit	Irritant
2-Methylpentane	Professio	Mild irritant
	nal	
	judgeme	
3-Methylpentane	nt	
5-tvietny/pentaire	Professio	Mild irritant
	nal	
	judgeme	
Magnesium Oxide	nt	
Audirestati Oxide	Professio	No significant irritation
	nal	5 ····
	judgeme	
Kylene	nt	
Carbon Black	Rabbit	Mild irritant
Ethylbenzene	Rabbit	No significant irritation
	Rabbit	Mild irritant
formaldehyde	official	Сопозіче
	classifica	
	tion	

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Ethyl Ketone		
Hexane	Rabbit	Severe irritant
Polychloroprene	Rabbit	Mild irritant
rotychlotopiene	Professio	No significant irritation
	nal	
	judgeme	
Heptane	nt	
reptaile	Professio	Moderate irritant
	nal	
	judgeme	1
Mothylausia	nt	
Methylcyclopentane	similar	Mild irritant
	compoun	
Foluene	ds	
	Rabbit	Moderate irritant
-Methylpentane	Professio	Moderate irritant
	nal	
	judgeme	
Math	nt	
-Methylpentane	Professio	Moderate irritant
	nal	The second second
	judgeme	
7-1	nt	
ylene	Rabbit	Mild irritant
arbon Black	Rabbit	No significant irritation
thylbenzene	Rabbit	Moderate irritant
	1	moderate inflatif

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

Formaldehyde	official classifica	Corrosive
	tion	

Skin Sensitization	Species	Value
Name	Human	Not sensitizing
Hexane	Guinea	Not sensitizing
Toluene	pig	
	Human	Not sensitizing
Ethylbenzene	Guinea	Sensitizing
Formaldehyde	pig	

Respiratory Sensitization	Species	Value
Name	Human	Some positive data exist, but the data are not
Formaldehyde		sufficient for classification

erm Cell Mutagenicity	Route	Value
Name		
	In Vitro	Not mutagenic
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Hexane	In Vitro	Not mutagenic
Heptane	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Magnesium Oxide	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Xylene	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not
Carbon Black		sufficient for classification
	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
Ethylbenzene		sufficient for classification
-	In Vitro	Some positive data exist, but the data are not
Formaldehyde		sufficient for classification
	In vivo	Mutagenic
Formaldehyde		

arcinogenicity	Route	Species	Value .
Name	Inhalation	Human	Not carcinogenic
Methyl Ethyl Ketone	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not
Hexane			sufficient for classification
	Dermal	Mouse	Some positive data exist, but the data are not
Toluene			sufficient for classification
	Ingestion	Rat	Some positive data exist, but the data are not
Toluene			sufficient for classification
	Inhalation	Mouse	Some positive data exist, but the data are not
Toluene			sufficient for classification
	Not	Human	Some positive data exist, but the data are not
Magnesium Oxide	Specified	and	sufficient for classification
	Į - ,	animal	
	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple	Not carcinogenic
Xylene		animal	
		species	to the the data are not
	Inhalation	Human	Some positive data exist, but the data are not
Xylene		l	sufficient for classification
	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Carbon Black	Killarati		

3MTM Super Weatherstrip and Gasket Adhesive - Black, P.N. 08008, 08581 05/12/15

Ethylbenzene			
	Inhalation	Multiple	Carcinogenic
	1	animal	
Formaldehyde	<u> </u>	species	
·	Not	Human	Carcinogenic
	Specified	and	
		animal	
Reproductive Toutet			

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name Methyl Ethyl Ketone	Route	Value	Specie	S Test Result	Exposure
Methyl Ethyl Ketone	Inhalation	to romaic reproduction	Rat	NOAEL 14.7	Duration 90 days
Methyl Ethyl Ketone	Inhalation	to to to mate reproduction	Rat	mg/l NOAEL 14.7	90 days
Hexane	Inhalation	but the data are not sufficient for classification	Rat	mg/l LOAEL 8.8 mg/l	during gestation
Hexane	Ingestion	Not toxic to development	Mouse	NOAEL 2,200	during organogene
Hexane	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	mg/kg/day NOAEL 0.7 mg/l	during gestation
	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140	90 days
Hexane Toluene	Inhalation	- Toproduction	Rat	mg/kg/day LOAEL 3.52	28 days
Toluene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	mg/I NOAEL Not available	occupational exposure
Toluene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.3 mg/l	1 generation
Foluene	Ingestion	Toxic to development	Rat	LOAEL 520	during
(ylene	Inhalation	Toxic to development	Human	mg/kg/day NOAEL Not available	gestation poisoning
	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 1,000	and/or abuse 103 weeks
ylene	Ingestion	Not toxic to male reproduction	Mouse	mg/kg/day NOAEL 1,000	103 weeks
ylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for	Human	mg/kg/day NOAEL Not available	occupational
ylene	Ingestion	classification Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesi
ylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for	Multiple animal	NOAEL Not available	during gestation
hylbenzene	Inhalation	Same positive dead	species Rat	NOAEL 4.3 mg/l	premating & during
rmaldehyde rmaldehyde	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg	gestation not applicable
manuenyde	Inhalation	Some marks I d	Rat	NOAEL 10	during gestation

Lactation

	Route	Species	Value
Name	Ingestion	Mouse	Does not cause effects on or via lactation
Xylene	Ingostion		

Target Organ(s)

ecific Target Orga lame	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Ethyl Ketone	Inhalation		May cause drowsiness or dizziness	official classifica	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	tion Human	NOAEL Not available	
		liver	classification Some positive data exist, but the	Rat	NOAEL Not	not applicable
Methyl Ethyl Ketone	Ingestion	nver	data are not sufficient for classification		available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,080 mg/kg	
Hexane	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not available	not available
	Inhalation	system depression respiratory irritation	dizziness Some positive data exist, but the	Rabbit	NOAEL Not	8 hours
Hexane	Imaiason	respiratory in the second	data are not sufficient for		available	
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 24.6 mg/l	8 hours
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous	May cause drowsiness or dizziness	Human	NOAEL Not available	
Methylcyclopentane	Inhalation	system depression central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
2-Methylpentane	Inhalation		May cause drowsiness or dizziness		NOAEL Not available	
2-Methylpentane	Inhalation		Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Methylpentane	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL Not available	
3-Methylpentane	Inhalatio	central nervous system depression	May cause drowsiness or dizziness		available	
3-Methylpentane	Inhalation		Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
3-Methylpentane	Inhalatio	n cardiac sensitization	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Magnesium Oxide	Inhalatio	n respiratory system	All data are negative	Human	available	8 hours
Xylene	Inhalatio	n auditory system	Causes damage to organs	Rat	LOAEL 6.3	6 nours

Xylene	Inhalation			1	mg/l	
Xylene		central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.5 mg/l	not available
Xylene Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal	NOAEL Not available	
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	species Rat	NOAEL 250 mg/kg	not applicable
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and	available NOAEL Not available	
Formaldehyde	Inhalation	respiratory system	Causes damage to organs	animal Rat	LOAEL 128	6 hours
Formaldehyde	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	ppm NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
Methyl Ethyl Ketone	Dermal	nervous system	All data are negative	Cuinti	110.1	Duration
Methyl Ethyl Ketone				Guinea pig	NOAEL Not available	31 weeks
· ·	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles	All data are negative	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	All data are negative	Rat	NOAEL 173	90 days
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	mg/kg/day NOAEL Not available	occupationa exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.76 mg/l	6 months
lexane	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 35.2 mg/l	13 weeks
łexane	Inhalation	auditory system immune system eyes	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Iexane	Inhalation	heart skin endocrine system	All data are negative	Rat	NOAEL 1.76 mg/l	6 months

lexane		peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
exane		endocrine system hematopoietic system liver immune system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	13 weeks
leptane	Inhalation	liver nervous system kidney and/or bladder	All data are negative	Rat	NOAEL 12 mg/l	26 weeks
Coluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	4 weeks
2-Methylpentane	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,000 mg/kg	28 days
3-Methylpentane	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 5.3 mg/l	14 weeks
3-Methylpentane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
3-Methylpentane	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,000 mg/kg	28 days

37.1						
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system hematopoietic system muscles kidney and/or bładder respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal	mg/kg/day NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	All data are negative	species Mouse	NOAEL, 1,000 mg/kg/day	103 weeks
Carbon Black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months
Formaldehyde	Dermal	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 80 mg/kg/day	60 weeks
ormaldehyde	Inhatation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 ppm	28 months
ormaldehyde	Inhalation	liver	Some positive data exist, but the	Rat	NOAEL 20	13 weeks

		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	data are not sufficient for classification		ppm	
Formaldehyde	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 15 ppm	3 weeks
Formaldehyde	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 10 ppm	13 weeks
Formaldehyde	Inhalation	endocrine system immune system muscles kidney and/or bladder	All data are negative	Rat	NOAEL 15 ppm	28 months
Formaldehyde	Inhalation	eyes vascular system	All data are negative	Rat	NOAEL 14.3 ppm	2 years
Formaldehyde	Inhalation	heart	All data are negative	Mouse	NOAEL 14.3 ppm	2 years
Formaldehyde	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 20 mg/kg/day	4 weeks
Formaldehyde	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	24 months
Formaldehyde	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 109 mg/kg/day	2 years
Formaldehyde	Ingestion	heart endocrine system hematopoietic system respiratory system vascular system	All data are negative	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	skin muscles eyes	All data are negative	Rat	NOAEL 109 mg/kg/day	2 years

Aspiration Hazard

Name	Value
Hexane	Aspiration hazard
Heptane	Aspiration hazard
Methylcyclopentane	Aspiration hazard
Toluene	Aspiration hazard
2-Methylpentane	Aspiration hazard
3-Methylpentane	Aspiration hazard
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
Toluene	108-88-3	5 - 10
Hexane	110-54-3	4 - 15
Hexane (Hexane)	110-54-3	4 - 15
Xylene	1330-20-7	1 - 5
Xylene (Benzene, 1,2-dimethyl-)	1330-20-7	1 - 5
Xylene (Benzene, 1,3-dimethyl-)	1330-20-7	1 - 5
Xylene (Benzene, 1,4-dimethyl-)	1330-20-7	1 - 5
Xylene (Benzene, dimethyl-)	1330-20-7	1 - 5
Ethylbenzene	100-41-4	0.1 - 1.0

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	C.A.S. No.	Classification
Ethylbenzene	100-41-4	Carcinogen
Toluene	108-88-3	Female reproductive toxin
Toluene	108-88-3	Developmental Toxin
Carbon Black	1333-86-4	Carcinogen
Formaldehyde	50-00-0	Carcinogen
Benzene	71-43-2	Male reproductive toxin
Benzene	71-43-2	Carcinogen
Benzene	71-43-2	Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:

08-0531-7

Version Number:

16.00

Issue Date:

05/12/15

Supercedes Date:

06/01/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

