

Diesel Fuel Anti-Gel

Safety Data Sheet

TOTAL
SOLUTIONS™

SECTION 1: Product and company identification

Product name : Diesel Fuel Anti-Gel
Use of the substance/mixture : Fuel: additive
Product code : 0654
Company : Total Solutions
P.O. Box 240014
Milwaukee, WI 53224 - USA
T (414) 354-6417
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
Acute Tox. 4 (Oral) H302
Skin Irrit. 2 H315
Eye Irrit. 2 H319
Muta. 1B H340
Carc. 1B H350
STOT SE 3 H335
STOT SE 3 H336
Asp. Tox. 1 H304

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Hazard statements (GHS-US) :

Precautionary statements (GHS-US) :

- : Danger
- : Flammable liquid and vapour
Harmful if swallowed
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
May cause drowsiness or dizziness
May cause genetic defects
May cause cancer
- : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, open flames, sparks. - No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment
Use explosion-proof electrical, lighting equipment
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing mist, spray.
Wash thoroughly after handling
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear eye protection, protective clothing, protective gloves.
If swallowed: Immediately call a doctor, a POISON CENTER
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If exposed or concerned: Get medical advice/attention.
Call a doctor, a POISON CENTER if you feel unwell
Rinse mouth.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.

Diesel Fuel Anti-Gel

Safety Data Sheet

TOTAL
SOLUTIONS™

If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Keep cool.
 Store locked up.
 Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
SOLVESSO 100	(CAS-No.) 64742-95-6	40-70	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
Trimethylbenzene	(CAS-No.) 25551-13-7	30-60	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Asp. Tox. 1, H304
Solvent naphtha (petroleum), heavy arom. cumene	(CAS-No.) 64742-94-5 (CAS-No.) 98-82-8	15-40 3-7	Asp. Tox. 1, H304 Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304
xylene	(CAS-No.) 1330-20-7	0.5-5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
naphthalene	(CAS-No.) 91-20-3	1-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Carc. 1B, H350 Aquatic Acute 1, H400
kerosine(petroleum), hydrodesulfurized	(CAS-No.) 64742-81-0	0.1-2	STOT SE 3, H336 Asp. Tox. 1, H304
cymenes	(CAS-No.) 25155-15-1	0.5-1.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a poison center or doctor/physician. Rinse mouth with water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer.
------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Diesel Fuel Anti-Gel

Safety Data Sheet

TOTAL
SOLUTIONS™

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed. May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Cramps. Nausea. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical powder. Carbon dioxide. Alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: vapors may travel long distances along ground before igniting/flashing back to vapor source.
Reactivity	: Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Isolate from fire, if possible, without unnecessary risk. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.
------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Protective goggles. Gloves. Protective clothing.
Emergency procedures	: Evacuate unnecessary personnel. No naked flames or sparks.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation. Take up liquid spill into inert absorbent material, e.g.: sand/earth. Clean contaminated surfaces with a soap solution.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Do not breathe vapors. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Handle and open the container with care. Keep away from sources of ignition - No smoking. Take precautions against electrostatic charges. Obtain special instructions before use. Remove contaminated clothing immediately.
Hygiene measures	: Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from: sparks, open flames, excessive heat.
Incompatible products	: Strong oxidizers.
Incompatible materials	: Sources of ignition. Heat sources.
Storage area	: Store away from heat. Store in a cool area. Store in a dry area. Store in a well-ventilated place. Keep locked up.

Diesel Fuel Anti-Gel

Safety Data Sheet



Special rules on packaging

: Keep only in original container. meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Trimethylbenzene (25551-13-7)		
ACGIH	ACGIH TWA (ppm)	25 ppm
ACGIH	Remark (ACGIH)	CNS impair; asthma; hematologic eff
cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	0.1 ppm
ACGIH	Remark (ACGIH)	Lung cancer; liver and lung dam; A2 (Suspected Human Carcinogen: Human data are accepted as adequate in quality but are conflicting or insufficient to classify the agent as a confirmed human carcinogen; OR, the agent is carcinogenic in experimental animals at dose(s), by route(s) of exposure, at site(s), of histologic type(s), or by mechanism(s) considered relevant to worker exposure. The A2 is used primarily when there is limited evidence or carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals with relevance to humans)
OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
naphthalene (91-20-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	Remark (ACGIH)	Hematologic eff; URT & eye irr; Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm
kerosine(petroleum), hydrodesulfurized (64742-81-0)		
ACGIH	ACGIH TWA (mg/m ³)	200 mg/m ³ (Application restricted to conditions in which there are negligible aerosol exposures)
ACGIH	Remark (ACGIH)	Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)

Diesel Fuel Anti-Gel

Safety Data Sheet

8.2. Exposure controls

Personal protective equipment

: Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Gloves. Safety glasses. Protective goggles. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear to hazy liquid. Colorless liquid.
Odor	: characteristic solvent odor
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 120 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.89 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: Not Determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Diesel Fuel Anti-Gel

Safety Data Sheet



Acute toxicity : Oral: Harmful if swallowed.

SOLVESSO 100 (64742-95-6)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit)
Trimethylbenzene (25551-13-7)	
LD50 oral rat	500 mg/kg
LD50 dermal rabbit	1100 mg/kg
xylene (1330-20-7)	
LC50 inhalation rat (ppm)	4550 ppmV/4h
ATE CLP (dermal)	1100 mg/kg body weight
ATE CLP (gases)	4550 ppmV/4h
ATE CLP (dust, mist)	1.5 mg/l/4h
cymenes (25155-15-1)	
LD50 oral rat	> 2000 mg/kg (Rat)
naphthalene (91-20-3)	
LD50 dermal rat	> 2500 mg/kg (Rat)
ATE CLP (oral)	500 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
xylene (1330-20-7)	
IARC group	3 - Not classifiable
naphthalene (91-20-3)	
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Cramps. Nausea. Vomiting.

SECTION 12: Ecological information

12.1. Toxicity

SOLVESSO 100 (64742-95-6)	
LC50 fish 1	18 mg/l (Pisces)
EC50 Daphnia 1	21 mg/l (Daphnia sp.)
naphthalene (91-20-3)	
LC50 fish 1	0.11 mg/l (96 h, Oncorhynchus mykiss, Literature study)
EC50 Daphnia 1	2.16 mg/l (48 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

SOLVESSO 100 (64742-95-6)	
Persistence and degradability	Readily biodegradable in water.
cymenes (25155-15-1)	
Persistence and degradability	Biodegradability in water: no data available.

Diesel Fuel Anti-Gel

Safety Data Sheet

TOTAL
SOLUTIONS™

naphthalene (91-20-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
Chemical oxygen demand (COD)	0.22 g O ₂ /g substance
ThOD	2.99 g O ₂ /g substance

12.3. Bioaccumulative potential

SOLVESSO 100 (64742-95-6)	
Log Pow	> 3
cymenes (25155-15-1)	
Bioaccumulative potential	No bioaccumulation data available.
naphthalene (91-20-3)	
BCF fish 1	23 - 168 (8 week(s), Cyprinus carpio, Literature study)
Log Pow	3.3 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Additional information

Other information : When transported by ground in non-bulk containers, this product utilizes the exception found under 49 CFR 173.150. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,2,4-trimethylbenzene	CAS-No. 95-63-6	10-30%
cumene	CAS-No. 98-82-8	3-7%
xylene	CAS-No. 1330-20-7	0.5-5%
naphthalene	CAS-No. 91-20-3	1-5%

1,2,4-trimethylbenzene (95-63-6)

Subject to reporting requirements of United States SARA Section 313

cumene (98-82-8)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 5000 lb

Diesel Fuel Anti-Gel

Safety Data Sheet

TOTAL
SOLUTIONS™

xylene (1330-20-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb

naphthalene (91-20-3)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb

⚠ WARNING

This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.