## SAFETY DATA SHEET



Revision Date 27-Mar-2015

"一个"的"大"的"大"的"大"。 "

Version 1

Product identifier

**Product Name** 

765-4674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

Other means of identification

**Product Code** Synonyms

21201 None

Recommended use of the chemical and restrictions on use

Recommended Use Uses advised against Lubricant

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

**ITW Permatex** 10 Columbus Blvd.

Hartford, CT 06106 USA

**Distributor** 

ITW Permatex Canada 35 Brownridge Road, Unit 1

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

**Company Phone Number** 

1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number

Chem-Tel: 800-255-3924 International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

### 2 HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral

Category 4

Label elements

**Emergency Overview** 

Warning

Harmful if swallowed



Appearance Silver

Physical state Paste

Odor Mild petroleum odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I Harmful to aquatic life with long lasting effects

Unknown acute toxicity

19.23275% of the mixture consists of ingredient(s) of unknown toxicity

### STATE THE ENGINE NO PROPERTY IN THE PROPERTY OF THE VIEWS

#### substance

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30 - 60	*
CALCIUM OXIDE	1305-78-8	10 - 30	*
GRAPHITE	7782-42-5	10 - 30	*
ALUMINIUM POWDER	7429-90-5	5 - 10	*
MINERAL OIL	8042-47-5	3 - 7	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

4 FIRST AID MEASURES

## 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT

(PTX80078) 8 OZ.

Skin contact

IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

## 5. HIREHTIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

<u>Unsuitable extinguishing media</u>

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge

None. None.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6 ACCIDENTALIRELEASE VIEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions** 

Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

### 7/2 HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials

Strong oxidizing agents, Acids, Alkali, Amines

## EXPOSURE CONSTRUCTORS IN THE CARGON CONTROL OF CARGON

### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	8811	
CALCIUM OXIDE	TWA: 2 mg/m³	OSHA PEL	NIOSH IDLH
1305-78-8	1 TAVY 5 HIGHIIA	TWA: 5 mg/m³	IDLH: 25 mg/m <sup>3</sup>
	1	(vacated) TWA: 5 mg/m³ not in	730/0.0
GRAPHITE	TWA: 2 mg/m³ speniseble to di	effect as a result of reconsideration	_
7782-42-5	TWA: 2 mg/m³ respirable fraction all forms except graphite fibers		IDLH: 1250 mg/m <sup>3</sup>
	an forms except grapfille libers	TVVA: 5 mg/m³ respirable fraction	TWA: 2.5 mg/m³ natural respirable
		synthetic	dust
	1	(vacated) TWA: 2.5 mg/m³	+40.
	1	respirable dust natural	
	ļ	(vacated) TWA: 10 mg/m³ total dust	
	j	synthetic	
	ĺ	(vacated) TWA: 5 mg/m³ respirable	
	1	fraction synthetic	
ALUMINIUM POWDER	TWA: 1 mg/m³ respirable fraction	TWA: 15 mppcf natural	
7429-90-5	The standard respirable fraction	TWA: 15 mg/m³ total dust	TWA: 5 mg/m³ Al
	İ	TWA: 5 mg/m³ respirable fraction	
		(vacated) TWA: 5 mg/m³ Al	
IOSH IDLH Immediately Dan	gerous to Life or Health	Aluminum	

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

Appropriate engineering controls

**Engineering Controls** 

Showers

Eyewash stations Ventilation systems

## Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

### 9VPHYSICALAND GHENICAL PROPERTIES Information on basic physical and chemical properties

Physical state

Paste

### 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

**Appearance** 

Odor

Odor threshold

Silver

**Property** 

Нα

Melting point / freezing point Boiling point / boiling range

Flash point **Evaporation rate** 

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Lower flammability limit:

Vapor pressure Vapor density Relative density Water solubility

Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature

Kinematic viscosity Dynamic viscosity **Explosive properties** Oxidizing properties

Mild petroleum odor No information available

Values\_ No information available

No information available No information available Not

determined

> 93 °C / > 200 °F

< 1

No information available

No information available No information available

<5 mm Hg

>1

1.17 Negligible

No information available No information available No information available No information available No information available No information available No information available No information available Remarks • Method

Tag Closed Cup Butyl acetate = 1

Air = 1

### Other Information

Softening point Molecular weight VOC Content (%)

Density **Bulk density**  No information available No information available

No information available No information available

## 10 STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Alkali, Amines

**Hazardous Decomposition Products** 

Carbon oxides

# AND THE PROPERTY OF THE PROPER

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Harmful if swallowed.

Chemical Name CALCIUM OXIDE 1305-78-8 MINERAL OIL 8042-47-5	Oral LD50 = 500 mg/kg (Rat) > 5000 mg/kg (Rat)	Dermal LD50 - -	Inhalation LC50 -
Information on toxicological			

### Information on toxicological effects

**Symptoms** 

No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. Chemical Name **ACGIH** NTP A2 OSHA

DISTILLATES Group 1 (PETROLEUM). HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

**Target Organ Effects** 

Central Vascular System (CVS), Eyes, Respiratory system, Skin.

## The following values are calculated based on chapter 3.1 of the GHS document .

1978 mg/kg

ATEmix (inhalation-vapor)

32255 mg/l

### 12 ECOLOGICALINFORMATION

#### **Ecotoxicity**

32.42995% of the mixture consists of components(s) of unknown hazards to the aquatic environment

	Algae/aquatic plants	hazards to the aquatic environme	ent
DISTILLATES (PETROLEUM),	- ground plants	Fish	Crustacea
HYDROTREATED HEAVY NAPHTHENIC		5000: 96 h Oncorhynchus mykiss mg/L LC50	The state of the s
64742-52-5		9/2 2000	EC50
CALCIUM OXIDE	_	1070: 00 t. 0	
1305-78-8		1070: 96 h Cyprinus carpio mg/L LC50 static	_
MINERAL OIL 8042-47-5	-	10000: 96 h Lepomis macrochirus	-
		mg/L LC50	
Persistence and degradability		···	

### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

### 21201 - 765-1674 NAPA ANTI-SEIZE LUBRICANT (PTX80078) 8 OZ.

**Mobility** 

No information available.

No information available.	
	Partition coefficient
Chemical Name	>6
MINERAL OIL	
8042-47-5	

#### Other adverse effects No information available

## YET DISPOSAL (GOVERNOUS MAINTENANTONS)

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

**US EPA Waste Number** 

Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

This product contains one of more substanted that	
	California Hazardous Waste Status
Chemical Name	Corrosive
CALCIUM OXIDE	
1305-78-8	Ignitable powder
ALUMINIUM POWDER	Igilitable polices
7429-90-5	

## WASTRANSPORTINFORMATION CO.

DOT

Proper shipping name:

Not regulated

<u>IATA</u>

Proper shipping name:

Not regulated

Proper shipping name:

Not regulated

## 2/15 REGULATIONY INFORMATION

International Inventories

**TSCA** DSL/NDSL Complies Complies

**EINECS/ELINCS** 

Complies

Natural substance **ENCS** Complies

**IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** 

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

ALUMINIUM POWDER - 7429-90-5  SARA 311/312 Hazard Categories  Acute health hazard  Chronic Health Hazard  Fire hazard  Sudden release of pressure hazard  Reactive Hazard  No  Reactive Hazard  No  Substitute SARA 313 - Threshold Values %  1.0  Yes  No  No  No  No		572 or Fall 572
NO	SARA 311/312 Hazard Categories  Acute health hazard Chronic Health Hazard Fire hazard Sudden release of pressure hazard	Yes No No

### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

### US State Regulations

### California Proposition 65

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	
CALCIUM OXIDE 1305-78-8	X	X	Pennsylvania X
GRAPHITE 7782-42-5	Х	Х	X
ALUMINIUM POWDER 7429-90-5	X	Х	X
MINERAL OIL 8012-95-1	Х	X	×
COPPER 7440-50-8	Х	X	×

EPA Pesticide Registration Number Not applicable

**NFPA** Health hazards 1 Flammability 1 Instability 0 <u>HMIS</u> Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 

27-Mar-2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet