SAFETY DATA SHEET



1. Identification

Product number

1000009282

Product identifier

SW725 WELDER'S ANTI-SPATTER SPRAY

Company information

Sprayway, Inc.

1000 INTEGRAM DR

Pacific, MO 63069 United States

Company phone

1-630-628-3000

Emergency telephone US

1-866-836-8855

Emergency telephone outside

1-952-852-4646

US

Version #

01

Recommended use

Not available.

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Flammable aerosols

Category 1

Health hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response

Wash hands after handling.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Propane		74-98-6	20 - 40
Other components below reportable levels			40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY
Product #: 1000009282 Version #: 01 Issue date: 11-12-2018

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Dizziness.

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with

water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol. Combustible.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable, Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Type Value Propane (CAS 74-98-6) PEL 1800 mg/m3 1000 ppm

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY

SDS US Product #: 1000009282 Version #: 01 Issue date: 11-12-2018

He	ACCIL	Thea	blode	Limit	Values
115	At Rill	i inres	รทกมก	I.IITTEE	vames

Components	Туре	Value		
Butane (CAS 106-97-8)	STEL	1000 ppm		
US. NIOSH: Pocket Guide to Che Components	emical Hazards Type	Value	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	,	
T (0.40.74.00.0)	TIALA	800 ppm		
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm		

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other

Wear suitable protective clothing.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Gas.

Form

Aerosol.

Color

Not available.

Odor Odor threshold

Not available. Not available.

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

range

662 °F (350 °C) estimated

Flash point

-156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits Flammability limit - lower

1.9 % estimated

(%)

Flammability limit - upper

9.5 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

70 - 80 psig @70F estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature Not available. Not available.

Viscosity

Not available.

Other information

Explosive properties

Not explosive.

Heat of combustion (NFPA

35,53 kJ/g estimated

30B)

Oxidizing properties

Not oxidizing.

Specific gravity

0.862 - 0.872 estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation

No adverse effects due to inhalation are expected.

Skin contact

No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation.

Eye contact Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dizziness.

Information on toxicological effects

Acute toxicity

Product Species **Test Results**

SW725 WELDER'S ANTI-SPATTER SPRAY

<u>Acute</u>

Inhalation

LC50

Rat

1316 mg/l/4h

Components

Species

Test Results

Butane (CAS 106-97-8)

Acute

Inhalation

LC50

Mouse

1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat

1355 mg/l

Propane (CAS 74-98-6)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat

1355 mg/l

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY

Product #: 1000009282 Version #: 01 Issue date: 11-12-2018

Test Results Components Species

658 ma/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs, Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity repeated exposure

Not classified.

Aspiration hazard

Not likely, due to the form of the product,

Species

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product SW725 WELDER'S ANTI-SPATTER SPRAY

Aquatic

Fish

LC50

Fish

2773 mg/L, 96 Hours

Test Results

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butane

2.89

Propane

2.36

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site, Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY

Product #: 1000009282 Version #: 01 Issue date: 11-12-2018

^{*} Estimates for product may be based on additional component data not shown.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity) Transport hazard class(es)

Class Subsidiary risk 2.1

Label(s) Packing group 2.1

Special precautions for user Not available.

Not applicable.

Special provisions Packaging exceptions N82 306

Packaging non bulk

None

Packaging bulk

None

IATA

UN number

UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable

Class Subsidiary risk 2.1

Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

No.

ERG Code

10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only

Allowed with restrictions.

Packaging Exceptions

LTD QTY

IMDG

UN number

UN1950 **AEROSOLS**

UN proper shipping name

Transport hazard class(es)

Class

Subsidiary risk

2.1

Label(s)

None

Packing group

Not applicable.

Environmental hazards

Marine pollutant

No.

EmS

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions

LTD QTY Not applicable.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Product name: SW725 WELDER'S ANTI-SPATTER SPRAY Product #: 1000009282 Version #: 01 Issue date: 11-12-2018



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY
Product #: 100009282 Version #: 01 Issue date: 11-12-2018

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-12-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Response

Composition / Information on Ingredients: Component Summary

Handling and storage: Conditions for safe storage, including any incompatibilities

Physical & Chemical Properties: Multiple Properties

Product name: SW725 WELDER'S ANTI-SPATTER SPRAY
Product #: 1000009282 Version #: 01 Issue date: 11-12-2018