Printing date 03/03/2020

Reviewed on 03/03/2020

1 Identification

- · Product identifier
- · Trade name: Sure AnchorTM I J51 Part A
- · Article number: 100908A
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Eye Irrit. 2A

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

Carc. 2

H351 Suspected of causing cancer.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:
- 2,3-epoxypropyl o-tolyl ether

titanium dioxide

· Hazard statements

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/03/2020 Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous d	components:	
25085-99-8	Diglycidyl ether of bisphenol A homopolymer	≥10-<90%
2210-79-9	2,3-epoxypropyl o-tolyl ether	≥2.5-<4%
471-34-1	calcium carbonate	<4.0%
67762-90-7	Hydrophobic silica	<3.25%
13463-67-7	titanium dioxide	≥0.1-<1.6%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Seek immediate medical advice.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 03/03/2020

Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- · Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

(Contd. on page 4)

Printing date 03/03/2020

Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

(Contd. of page 3)

471-34-1 calcium carbonate

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m3

*total dust **respirable fraction

TLV TLV withdrawn

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Liquid

Color:

Clear

· Odor:

Mild

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

Undetermined.

· Flash point:

>93 °C (>199.4 °F)

· Flammability (solid, gaseous):

Not applicable.

· Decomposition temperature:

Not determined.

· Auto igniting:

Lower:

Product is not selfigniting.

· Danger of explosion: · Explosion limits:

Product does not present an explosion hazard.

Not determined.

(Contd. on page 5)

Printing date 03/03/2020

Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

	(Contd. of pag
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.2 g/cm³ (10.014 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	tter): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	1,000,000 mPas
Kinematic:	Not determined.
· Solvent content:	
Solids content:	100.0 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Contains less than 10 g/L

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

 Oral
 LD50
 5,000 mg/kg (rat)

 Dermal
 LD50
 20,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 6)

Printing date 03/03/2020 Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

Carcinogenic categories

IARC (International Agency for Research on Cancer)

14807-96-6 Talc

13463-67-7 titanium dioxide

7631-86-9 silicon dioxide, chemically prepared

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, ADN, IATA

Not Regulated UN3082

· IMDG

(Contd. on page 7)

Printing date 03/03/2020

Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

	(Contd. of page
UN proper shipping name DOT, ADR, ADN, IATA IMDG	Not Regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIL N.O.S. (epoxy resin), MARINE POLLUTANT
Transport hazard class(es)	
DOT, ADR, ADN, IATA	
· Class	Not Regulated
· IMDG	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group · DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No Symbol (fish and tree)
	Symbol (lish and tree)
· Special precautions for user · EMS Number:	F- A , S - F
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL736 and the IBC Code	778 Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Remarks:	Not Regulated for Transport.
· ADR	N . D I I
· Remarks: · U.S. Domestic Ground Shipments:	Not Regulated for Transport. Same as listed for Standard Shipments above.
· U.S. Domestic Ground Snipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per	Same as usica joi sianaara surpniems avove.
container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
· IMDG	г
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	Not Regulated

Printing date 03/03/2020 Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

(Contd. of page 7)

Sara	
Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings): This product may contain 1 or more toxic chemicals subject to the reporti Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CF	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	<i></i>
25085-99-8 Diglycidyl ether of bisphenol A homopolymer	ACTIV
2210-79-9 2,3-epoxypropyl o-tolyl ether	ACTIV
471-34-1 calcium carbonate	ACTIV
67762-90-7 Hydrophobic silica	ACTIV
14807-96-6 Talc	ACTIV
13463-67-7 titanium dioxide	ACTIV
7631-86-9 silicon dioxide, chemically prepared	ACTIV
21645-51-2 aluminium hydroxide	ACTIV
63148-62-9 Siloxanes and Silicones, di-Me	ACTIV
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to the State of California (Prop. 65) to cause cancer:	
13463-67-7 titanium dioxide	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value established by ACGIH)	
14807-96-6 Talc	A
13463-67-7 titanium dioxide	
MAK (German Maximum Workplace Concentration)	
14807-96-6 Talc	3
13463-67-7 titanium dioxide	3.
NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	

Printing date 03/03/2020

Reviewed on 03/03/2020

Trade name: Sure AnchorTM I J51 - Part A

(Contd. of page 8)

· Hazard pictograms





- · Signal word Warning
- · Hazard-determining components of labeling:

2,3-epoxypropyl o-tolyl ether

titanium dioxide

· Hazard statements

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 03/03/2020 / 217
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3